

# Nagios XI - Uploaded plugin returns "/bin/bash^M: bad interpreter: No such file or directory"

Article Number: 474 | Rating: Unrated | Last Updated: Tue, Dec 18, 2018 at 5:33 PM

## Problem Description

After uploading a plugin (`check_apc_pdu_load.sh` for example), the following error is produced:

The following error message is produced:

```
-bash: ./check_apc_pdu_load.sh: /bin/bash^M: bad interpreter: No such file or directory
```

This is caused by the file being in a "Windows" format instead of a "Unix" format. It has to do with the line endings / carriage returns.

## Resolving The Problem

To resolve the problem you will convert the file to a Unix format. Execute the following steps from an SSH session as a user with root privileges.

The first step is to install the required package:

**RHEL | CentOS | Oracle Linux**

```
yum install -y dos2unix
```

**Debian | Ubuntu**

```
apt-get install -y dos2unix
```

The next step is to convert the file to a Unix format:

```
dos2unix /usr/local/nagios/libexec/check_apc_pdu_load.sh
```

This will output:

```
dos2unix: converting file /usr/local/nagios/libexec/check_apc_pdu_load.sh to UNIX format ...
```

After completing these steps the plugin should execute as intended.

## Final Thoughts

For any support related questions please visit the [Nagios Support Forums](http://support.nagios.com/forum/) at:

<http://support.nagios.com/forum/>

Posted by: tlea - Thu, Feb 25, 2016 at 12:26 AM. This article has been viewed 3911 times.

Online URL: <https://support.nagios.com/kb/article/nagios-xi-uploaded-plugin-returns-bin-bash^m-bad-interpretor-no-such-file-or-directory-474.html>